


KM 110-390 C2+

3-fach Kernzug, Luftventil 1-fach,
Auswerferplattensicherung,
Werkzeugheißkanal 6-fach,
Druckspeicher, verschleißarme
Plastifizierung, Wasserbatterie 8-
fach, Euromap 12-Schnittstelle,
Maschinenschuhe, komplette
Dokumentation



General

Manufacturer	Krauss Maffei
Year of manufacture	2003
Time of delivery	after arrangement
Freight base	EXW D-31535 Neustadt
Type	KM 110-390 C2+
Status	used

Technical data

Closing force (kN)	<u>1100 kN</u>
Clamping plate (mm)	<u>745×770</u>
Spar spacing (mm)	<u>470×470</u>
Installation height (mm)	<u>300 mm</u>
Panel distance (mm)	<u>900</u>
Control System	<u>MC4</u>
Hours of operation	<u>ca. 80.000</u>
Language	<u>german</u>

Injection unit

Screw diameter (mm)	<u>35</u>
Spray pressure (bar)	<u>2429</u>
Displacement (cm³)	<u>156</u>
Pump drive power (kW)	<u>18,5</u>
Heating power (kW)	<u>12</u>
Oil filling (l)	<u>345</u>
Dimension (m)	<u>4,30 x 1,50 x 2,20</u>
Total weight (to.)	<u>5,8</u>
Painting	<u>RAL 9002/5002</u>



